



Test Report : DETN01L-12N

1W SMD Package DC-DC Unregulated Converter

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

Other test

DESIGN VERIFY TEST
OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-5.0% ~ +5.0 % (Max)	I/P:5VDC O/P:FULL LOAD Ta:25°C	-1.27% -0.98%	P
2	RIPPLE & NOISE	100 mVp-p (Max)	I/P:5VDC O/P:FULL LOAD Ta:25°C	22 mV 21 mV	P
3	LINE REGULATION	-12% ~ +12% (Max)	I/P:4.5VDC~5.5VDC O/P:FULL LOAD Ta:25°C	-11.24% ~ +11.22% -11.23% ~ +11.18%	P
4	LOAD REGULATION	-8% ~ +8% (Max)	I/P:5VDC O/P:10% LOAD~FULL LOAD Ta:25°C	-2.77% ~ +3.28% -2.69% ~ +3.19%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	EFFICIENCY	80% (Typ)	I/P:5VDC O/P:FULL LOAD Ta:25°C	81.29%	P
2	DC CURRENT	257 mA / FULL LOAD (Max) 28 mA / NO LOAD (Max)	I/P:5VDC O/P:NO / FULL LOAD Ta:25°C	245.6 mA / FULL LOAD 26.37 mA / NO LOAD	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	SHORT PROTECTION	5 second max	I/P:5.5VDC O/P:FULL LOAD Ta:25°C	OK	P

SAFETY TEST
SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:3K VDC/min	I/P-O/P:3K VDC/min Ta:25°C	I/P-O/P: 0.002mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>10GΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>10GΩ NO DAMAGE	P

OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-HDBK-217F,GB,25°C TOTAL FAILURE RATE : 0.95693 M.T.B.F : 1045 KHRS			P

TEST RESULT	TESTER	APPROVAL
PASS	ARCHEN HSIAO	PETER CHENG