



Test Report: IRM-30-48

30W AC-DC PCB-Mount Green Power Module

■ DESIGN VERIFY TEST

Output Function Test
Input Function Test
Protection Function Test
Control Function Test
Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test
E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

■ DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1: 300 mVp-p (Max)	I/P:230VAC O/P:FULL LOAD Ta:25 ~	V1: 60 mVp-p (Max)	P
2	OUTPUT VOLTAGE TOLERANCE	V1: 2.5 %~ -2.5 % (Max)	I/P: 100VAC /305VAC O/P:FULL/ MIN. LOAD Ta:25 ~	V1: 0%~0.01 %	P
3	LINE REGULATION	V1: 0.5 %~ -0.5 % (Max)	I/P: 100VAC~ 305VAC O/P:FULL LOAD Ta:25 ~	V1: 0 %~0 %	P
4	LOAD REGULATION	V1: 0.5%~ -0.5 % (Max)	I/P: 230VAC O/P:FULL ~MIN LOAD Ta:25 ~	V1: 0.012 %~0.012-%	P
5	SET UP TIME	230VAC/1000ms (Max) 115VAC/1500ms (Max)	I/P: 230VAC/115VAC O/P:FULL LOAD Ta:25 ~	230VAC/101.385 ms 115VAC/ 292ms	P
6	RISE TIME	230VAC/30ms (Max) 115VAC/30ms (Max)	I/P: 230VAC/115VAC O/P:FULL LOAD Ta:25 ~	230VAC/17.760ms 115VAC/18.136 ms	P
7	HOLD UP TIME	230VAC/40ms (Typ) 115VAC/12ms(Typ)	I/P: 230VAC/115VAC O/P:FULL LOAD Ta:25 ~	230VAC/83.673ms 115VAC/18.513ms	P
8	OVER/UNDERSHOOT TEST	< ±5%	I/P: 230VAC O/P:FULL LOAD Ta:25 ~	< 5%	P
9	DYNAMIC LOAD	V1: 4800 mVp-p	I/P: 230VAC O/P:(1)FULL /Min LOAD 90%DUTY/1KHZ (2) (1)FULL /Min LOAD 90%DUTY/3KHZ (3)FULL /Min LOAD 90%DUTY/5KHZ (4)FULL /Min LOAD 50%DUTY/120HZ Ta:25 ~	442mVp-p 150mVp-p 122mVp-p 1060mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	85VAC~305VAC	I/P:TESTING O/P:FULL LOAD Ta:25 ~	60.2VAC~305VAC	P
			I/P: (1)LOW-LINE=3V=82 V HIGH-LINE=305 V O/P:FULL/MIN LOAD ON: 30 Sec OFF: 30 Sec 10MIN (2)230Vac ON: 0.5 Sec OFF: 0.5 Sec 20MIN (3)230Vac ON:3Sec OFF:3Sec 12HOURS (POWER ON/OFF NO DAMAGE)	TEST:OK	

2	INPUT FREQUENCY RANGE	47HZ ~440 HZ NO DAMAGE OSC	I/P:100 VAC ~305 VAC O/P:FULL-MIN LOAD Ta:25 ~	TEST:OK	P
3	EFFICIENCY	90 % (TYP)	I/P:230 VAC O/P:FULL LOAD Ta:25 ~	92.19%	P
4	INPUT CURRENT	230V/ 0.5 A (Typ) 115V/ 0.75A (Typ) 277V/ 0.375A (Typ)	I/P: 230 VAC/115VAC/277VAC O/P:FULL LOAD Ta:25 ~	I = 0.269A/ 230VAC I = 0.494A/ 115VAC I = 0.225A/ 277VAC	P
5	INRUSH CURRENT	230V/ 40A (Typ) 115V/ 20A (Typ) COLD START	I/P:230VAC/115VAC O/P:FULL LOAD Ta:25 ~	I =30.992A/ 230VAC I =10A/ 115VAC	P
6	NO LOAD CONSUMPTION	<0.1W	I/P: 240 VAC/115VAC O/P:NO LOAD Ta:25 ~	0.052W /240V 0.040W /115V	P
7	LEAKAGE CURRENT	<0.25 mA/ 277VAC	I/P 277 VAC O/P Min LOAD Ta 25 ~	L-FG: 0.011mA N-FG: 0.011mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	105%~160% RATED OUTPUT POWER	I/P: 230VAC I/P: 115VAC O/P:TESTING Ta:25 ~	119.05%/ 230VAC 128.57%/115VAC Hiccup Mode	P
2	OVER VOLTAGE PROTECTION	CH:50.4V~64V(Typ)	I/P:230VAC O/P:MIN LOAD Ta:25 ~	53.4V Shut off o/p voltage, clamping by zener diode	P
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 305VAC O/P: FULL LOAD Ta:25 ~	NO DAMAGE Hiccup Mode	P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q1 Rated 8A/600V	I/P High-Line= 305 V O/P (1)Full Load Turn on (2) Output Short (3)Full load continue Ta 25 ~	(1) 482V (2) 544V (3) 480V	P
2	Diode Peak Voltage	D100 Rated 10A/400V	I/P High-Line= 305 V O/P (1)Full Load Turn on (2)Output Short (3)Full load continue Ta 25 ~	(1)308V (2)278V (3)308V	P
3	Input Capacitor Voltage	C5 Rated: : 56 · /400 V	I/P High-Line= 305 V O/P (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta 25 ~	(1)364V (2)366V (3)364V	P

4	Control IC Voltage Test	PWM IC U1 Rated 24V	I/P High-Line= 305 V O/P (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta 25 ~	(1)17.5V (2) 16.8V (3) 17.5V	P
---	-------------------------	------------------------	---	------------------------------------	---

■ SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P 4 KVAC/min	I/P-O/P 4.4 KVAC/min Ta 25 ~	I/P-O/P 2.21 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P 500VDC>100MΩ	I/P-O/P 500 VDC Ta 25 ~/70%RH	I/P-O/P 9999 MΩ NO DAMAGE	P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	BS EN/EN61000-3-2 CLASS A	I/P 230 VAC/50HZ O/P FULL LOAD Ta 25 ~	PASS	P
2	CONDUCTION	BS EN/EN55032(CISPR32) CNS13438 CLASS B	I/P 230 VAC (50HZ) O/P FULL/50% LOAD Ta 25 ~	PASS Test by certified Lab	P
3	RADIATION	BS EN/EN55032(CISPR32) CNS13438 CLASS B	I/P 230 VAC (50HZ) O/P FULL LOAD Ta 25 ~	PASS Test by certified Lab	P
4	E.S.D	BS EN/EN61000-4-2 AIR 8KV / Contact 4KV	I/P 230 VAC/50HZ O/P FULL LOAD Ta 25 ~	CRITERIA A	P
5	E.F.T	BS EN/EN61000-4-4 INPUT 2KV	I/P 230 VAC/50HZ O/P FULL LOAD Ta 25 ~	CRITERIA A	P
6	SURGE	BS EN/EN61000-4-5 L-N 2KV	I/P 230 VAC/50HZ O/P FULL LOAD Ta 25 ~	CRITERIA A	P
7	Test by certified Lab Test Report Prepare				

■ RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	TEMPERATURE RISE TEST	MODEL IRM-30-24 1. ROOM AMBIENT BURN-IN 1 HRS I/P 230VAC O/P FULL LOAD Ta= 29.2°C 2. HIGH AMBIENT BURN-IN 1 HRS I/P 230VAC O/P FULL LOAD Ta=51.5°C			P

				<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta= 29.2 ~</th> <th>HIGH AMBIENT Ta= 51.5 ~</th> </tr> </thead> <tbody> <tr><td>1</td><td>D100</td><td>67.3°C</td><td>85.2°C</td></tr> <tr><td>2</td><td>T1</td><td>66.1°C</td><td>83.8°C</td></tr> <tr><td>3</td><td>C106</td><td>53.7°C</td><td>72.0°C</td></tr> <tr><td>4</td><td>C105</td><td>61.8°C</td><td>79.7°C</td></tr> <tr><td>5</td><td>C40</td><td>60.0°C</td><td>77.8°C</td></tr> <tr><td>6</td><td>Q1</td><td>63.9°C</td><td>82.0°C</td></tr> <tr><td>7</td><td>D5</td><td>62.3°C</td><td>80.3°C</td></tr> <tr><td>8</td><td>D40</td><td>58.4°C</td><td>76.3°C</td></tr> <tr><td>9</td><td>C5</td><td>59.8°C</td><td>77.5°C</td></tr> <tr><td>10</td><td>BD1</td><td>58.6°C</td><td>76.6°C</td></tr> <tr><td>11</td><td>LF2</td><td>53.9°C</td><td>72.0°C</td></tr> <tr><td>12</td><td>LF1</td><td>52.7°C</td><td>69.9°C</td></tr> <tr><td>13</td><td>L100</td><td>54.8°C</td><td>73.2°C</td></tr> <tr><td>14</td><td>D6</td><td>61.4°C</td><td>79.4°C</td></tr> <tr><td>15</td><td>D42</td><td>54.6°C</td><td>72.8°C</td></tr> <tr><td>16</td><td>D43</td><td>54.8°C</td><td>72.9°C</td></tr> <tr><td>17</td><td>1 CASE</td><td>50.6°C</td><td>69.1°C</td></tr> </tbody> </table>		NO	Position	ROOM AMBIENT Ta= 29.2 ~	HIGH AMBIENT Ta= 51.5 ~	1	D100	67.3°C	85.2°C	2	T1	66.1°C	83.8°C	3	C106	53.7°C	72.0°C	4	C105	61.8°C	79.7°C	5	C40	60.0°C	77.8°C	6	Q1	63.9°C	82.0°C	7	D5	62.3°C	80.3°C	8	D40	58.4°C	76.3°C	9	C5	59.8°C	77.5°C	10	BD1	58.6°C	76.6°C	11	LF2	53.9°C	72.0°C	12	LF1	52.7°C	69.9°C	13	L100	54.8°C	73.2°C	14	D6	61.4°C	79.4°C	15	D42	54.6°C	72.8°C	16	D43	54.8°C	72.9°C	17	1 CASE	50.6°C	69.1°C		
NO	Position	ROOM AMBIENT Ta= 29.2 ~	HIGH AMBIENT Ta= 51.5 ~																																																																												
1	D100	67.3°C	85.2°C																																																																												
2	T1	66.1°C	83.8°C																																																																												
3	C106	53.7°C	72.0°C																																																																												
4	C105	61.8°C	79.7°C																																																																												
5	C40	60.0°C	77.8°C																																																																												
6	Q1	63.9°C	82.0°C																																																																												
7	D5	62.3°C	80.3°C																																																																												
8	D40	58.4°C	76.3°C																																																																												
9	C5	59.8°C	77.5°C																																																																												
10	BD1	58.6°C	76.6°C																																																																												
11	LF2	53.9°C	72.0°C																																																																												
12	LF1	52.7°C	69.9°C																																																																												
13	L100	54.8°C	73.2°C																																																																												
14	D6	61.4°C	79.4°C																																																																												
15	D42	54.6°C	72.8°C																																																																												
16	D43	54.8°C	72.9°C																																																																												
17	1 CASE	50.6°C	69.1°C																																																																												
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P 230 VAC O/P 114 LOAD Ta 25 ~	TEST OK	P																																																																										
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P 305VAC/100VAC O/P 100 LOAD Ta= -30 ~	TEST OK	P																																																																										
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL50 ~ NO DAMAGE	I/P 305 VAC O/P FULL LOAD Ta=50 ~ HUMIDITY= 95 %R.H	TEST OK	P																																																																										
5	TEMPERATURE COEFFICIENT	±0.03%/ (0~50 ~)	I/P 230 VAC O/P FULL LOAD	0%/ (0~50 ~)	P																																																																										
6	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK	P																																																																										
7	THERMAL SHOCK TEST	1. Thermal shock Temperature : -30°C~ +70°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec		OK	P																																																																										
8	VIBRATION TEST	1 Carton & 1 Set (1) Waveform Sine Wave (2) Frequency 10~500Hz (3) Sweep Time 12min/sweep cycle (4) Acceleration 2G (Blank) /5G (ST) (5) Test Time 60min in each axis (X.Y.Z) (6) Ta 25 ~		TEST OK	P																																																																										



9	CAPACITOR LIFE CYCLE	SUPPOSE C105 IS THE MOST CRITICAL COMPONENT (1) I/P 230VAC O/P FULL LOAD Ta=25 ~ LIFE TIME (2) I/P 230VAC O/P FULL LOAD Ta=50 ~ LIFE TIME (3) I/P 230VAC O/P 75% LOAD Ta=50 ~ LIFE TIME (4) I/P 230VAC O/P 50% LOAD Ta=50 ~ LIFE TIME	(1) 152437HRS (2) 36569HRS (3) 54096HRS (4) 91433HRS	P
10	MTBF	MIL-HDBK-217F NOTICE S2 PARTS COUNT TOTAL FAILURE RATE 593.3K HRS		P
11	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure (Expected Life): Above 30,000 hours @ TA 50 ~		P

2007/3/20 A50-S014

SAMPLE	TEST RESULT	TESTER	APPROVAL
PRODUCT SAMPLE	PASS	FRANK	WANGDZ