

Model : SKE10B-05 10W DC-DC Single Output Converter
 V1 : 5V /200~2000mA

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-2%~+2% (Max)	I/P:24VDC O/P:50% LOAD Ta:25°C	-0.4%	P
2	RIPPLE & NOISE	50mVp-p (Max)	I/P:24VDC O/P:FULL LOAD Ta:25°C	15mV	P
3	LINE REGULATION	-0.3%~+0.3% (Max)	I/P:18VDC~36VDC O/P:FULL LOAD Ta:25°C	-0%~+0%	P
4	LOAD REGULATION	-0.5%~+0.5% (Max)	I/P:24VDC O/P:MIN~FULL LOAD Ta:25°C	-0%~+0%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	DC VOLTAGE RANGE	18VDC~36VDC (Typ)	I/P:TESTING O/P:FULL LOAD Ta:25°C	12.7V~36V	P
2	EFFICIENCY	79% (Typ)	I/P:24VDC O/P:FULL LOAD Ta:25°C	80.8%	P
3	DC CURRENT	530mA (Max)	I/P:24VDC O/P:FULL LOAD Ta:25°C	513mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	160%~250% (Max)	I/P:24VDC O/P:TESTING Ta:25°C	187% Hiccup Mode Reset Auto Recovery	P
2	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P:24VDC O/P:FULL LOAD Ta:25°C	NO DAMAGE Hiccup Mode Reset Auto Recovery	P

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT	
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 15HRS I/P:24VDC O/P:FULL LOAD Ta=25°C			P	
			Position	P/N		TEMP Ta=25°C
			CASE	SKE10B-05		39.3°C

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1KVDC/min	I/P-O/P:1KVDC/min Ta:25°C	I/P-O/P:0.02mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500VDC Ta:25°C	I/P-O/P:30GΩ NO DAMAGE	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2003.9.16	SKE10B-05	PASS	FRANK.CHEN	MAX LIN