

# CERTIFICATE

Issued to:  
Applicant:  
**MEAN WELL Enterprises Co., Ltd.**  
No.28, Wuquan 3rd Rd, Wugu District  
24891 New Taipei City, Taiwan

Licensee:  
**MEAN WELL Enterprises Co., Ltd.**  
No.28, Wuquan 3rd Rd, Wugu District  
24891 New Taipei City, Taiwan

Product : Independent LED driver  
Trade name(s) : MEAN WELL  
Type(s)/model(s) : XLG-320-L, XLG-320-L-A, XLG-320-L-AB, XLG-320-L-DA2, XLG-320-L-DA2-A, XLG-320-M, XLG-320-M-A, XLG-320-M-AB, XLG-320-M-DA2, XLG-320-M-DA2-A, XLG-320I-L-DA2, XLG-320I-L-DA2-A, XLG-320I-M-DA2 and XLG-320I-M-DA2-A

The product and any acceptable variation thereto as specified in the Annex to this certificate and the documents therein referred to.

DEKRA hereby declares that the above-mentioned product has been certified on the basis of:

- a type test according to EN 61347-2-13:2014, EN 61347-2-13:2014/A1:2017, EN 61347-1:2015, EN 61347-1:2015/A1:2021 and EN IEC 62384:2020
- an inspection of the factory location according to CENELEC Operational Document CIG 021
- a DEKRA certification agreement with the number 2175773


DEKRA hereby grants the right to use the ENEC certification mark.

The ENEC certification mark may be applied to the product as specified in this certificate for the duration and under the conditions of the ENEC certification agreement.

This certificate is issued on 3 May 2023 and expires upon withdrawal of one of the above mentioned standards.

Certificate number: 35-123429 REV.1

DEKRA Certification B.V.



B.T.M. Holtus  
Managing Director



K Xu  
Certification Manager

© Integral publication of this certificate is allowed

ACCREDITED BY THE  
DUTCH ACCREDITATION  
COUNCIL



**SPECIFICATION OF THE CERTIFIED PRODUCT****Product data**

Product	: Independent LED driver
Trade name(s)	: MEAN WELL
Type(s)/model(s)	: XLG-320-L, XLG-320-L-A, XLG-320-L-AB, XLG-320-L-DA2, XLG-320-L-DA2-A, XLG-320-M, XLG-320-M-A, XLG-320-M-AB, XLG-320-M-DA2, XLG-320-M-DA2-A, XLG-320I-L-DA2, XLG-320I-L-DA2-A, XLG-320I-M-DA2 and XLG-320I-M-DA2-A
Rated input voltage	: 120-277 V~
Rated input current	: 3,6 A
Rated frequency	: 50/60 Hz
Max. case temperature (tc)	: 85 °C
Power factor	: 0,95
Class of insulation	: Class I
Degree of protection	: IP67
Additional information	: Thermal, short-circuit and overload protection. Isolating

**Product data – type XLG-320-L, XLG-320-L-A and XLG-320-L-AB**

Output Rated	: max.340 Vdc, 150-300 Vdc, 1,05-1,4 A, constant current
Rated power	: 315 W
Ambient temperature (ta)	: 35 °C when input: 120-200 V~, 45 °C when input: 200-277 V~

**Product data – type XLG-320-L-DA2 and XLG-320I-L-DA2**

Output Rated	: Max. 340 Vdc, 150-300 Vdc, 1,05-1,4 A, constant current
Rated power	: 315 W
Ambient temperature (ta)	: 40 °C when input: 120-200 V~, 45 °C when input: 200-277 V~, 176-280 Vdc

**Product data – type XLG-320-L-DA2-A and XLG-320I-L-DA2-A**

Output Rated	: Max. 340 Vdc, 150-300 Vdc, 1,05-1,4 A, constant current
Rated power	: 315 W
Ambient temperature (ta)	: 35 °C when input: 120-200 V~, 45 °C when input: 200-277 V~, 176-280 Vdc

**Product data – type XLG-320-M, XLG-320-M-A and XLG-320-M-AB**

Output Rated	: Max. 180 Vdc, 74-148 Vdc, 2,1-2,8 A, constant current
Rated power	: 310,8 W
Ambient temperature (ta)	: 35 °C when input: 120-200 V~, 45 °C when input: 200-277 V~

**Product data – type XLG-320-M-DA2 and XLG-320I-M-DA2**

Output Rated	: Max. 180 Vdc, 74-148 Vdc, 2,1-2,8 A, constant current
Rated power	: 310,8 W
Ambient temperature (ta)	: 40 °C when input: 120-200 V~, 45 °C when input: 200-277 V~, 176-280 Vdc

**Product data – type XLG-320-M-DA2-A and XLG-320I-M-DA2-A**

Output Rated	: Max. 180 Vdc, 74-148 Vdc, 2,1-2,8 A, constant current, with auxiliary output (AUX: 12 Vdc, 0,25 A)
Rated power	: 310,8 W
Ambient temperature (ta)	: 35 °C when input: 120-200 V~, 45 °C when input: 200-277 V~, 176-280 Vdc

**TESTS****Test requirements**

EN 61347-2-13:2014  
EN 61347-2-13:2014/A1:2017  
EN 61347-1:2015  
EN 61347-1:2015/A1:2021  
EN IEC 62384:2020

**Test result**

The test results are laid down in DEKRA test file 439981000.

**Additional information**

This certificate replaces certificate No. 35-123429 which we hereby declare invalid.

The list of components is laid down in test report 4399810.51, 4399810.52.

**Conclusion**

The examination proved that all requirements were met.

**Factory locations**

YONGDEN TECHNOLOGY CORPORATION  
345 MacArthur HighWay Tabang,  
3015 Guiguinto, Bulacan, The Philippines

MEAN WELL (GUANGZHOU) Electronics Co., Ltd.  
No.11 Jingu South Road, Huadu District,  
510890 Guangzhou Guangdong, China

Trade name(s) : MEAN WELL stands for



## Model list

Models	Input	Output	ta	Remark	Rear cover (with or without plastic cap)
XLG-320-M	120-277 V~, 50/60 Hz, 3,6 A, $\lambda$ : 0,95	Constant current; Max. 180 Vdc, 74-148 Vdc, 2,1-2,8 A, Rated Power: 310,8 W	45 °C (Input: 200-277 V~) 35 °C (Input: 120-200 V~)	Non-dimmable	Without
XLG-320-M-A				Non-dimmable	With
XLG-320-M-AB				Dimmable	With
XLG-320-L	120-277 V~, 50/60 Hz, 3,6 A, $\lambda$ : 0,95	Constant current; Max. 340 Vdc, 150-300 Vdc, 1,05-1,4 A, Rated Power: 315 W	45 °C (Input: 200-277 V~) 35 °C (Input: 120-200 V~)	Non-dimmable	Without
XLG-320-L-A				Non-dimmable	With
XLG-320-L-AB				Dimmable	With
XLG-320-M-DA2	120-277 V~, 176-280 Vdc, 50/60 Hz, 3,6 A, $\lambda$ : 0,95	Constant current; Max. 180 Vdc, 74-148 Vdc, 2,1-2,8 A, Rated Power: 310,8 W	45 °C (Input: 200-277 V~) 40 °C (Input: 120-200 V~, 176-280 Vdc)	Dimmable	With
XLG-320I-M-DA2				Dimmable	With
XLG-320-M-DA2-A		Constant current; Max. 180 Vdc, 74-148 Vdc,	45 °C (Input: 200-277 V~) 35 °C (Input:	Dimmable	With

XLG-320I-M-DA2-A		2,1-2,8 A, Rated Power: 310,8 W, Aux: 12 Vdc, 0,25 A	120-200 V~, 176-280 Vdc)	Dimmable	With
XLG-320-L-DA2	120-277 V~, 176-280 Vdc, 50/60 Hz, 3,6 A, $\lambda$ : 0,95	Constant current; Max. 340 Vdc, 150-300 Vdc, 1,05-1,4 A, Rated Power: 315 W	45 °C (Input: 200-277 V~)	Dimmable	With
XLG-320I-L-DA2			40 °C (Input: 120-200 V~, 176-280 Vdc)	Dimmable	With
XLG-320-L-DA2-A		Constant current; Max. 340 Vdc, 150-300 Vdc, 1,05-1,4 A, Rated Power: 315 W, Aux: 12 Vdc, 0,25 A	45 °C (Input: 200-277 Vac)	Dimmable	With
XLG-320I-L-DA2-A			35 °C (Input: 120-200 V~, 176-280 Vdc)	Dimmable	With
<p>Remark: "XLG-320" and "XLG-320I" models have same PCB layout and circuit diagram. The major differences among them are with or without discharge tube and rating of some components.</p>					